



## **ASW AUTOMATIC TRANSMISSION FLUID**

### **APPLICATION**

- For use in slip-controlled lock-up transmissions made by Aisin-Warner.
- Controlled friction properties for smooth and efficient transmission of power over a wide temperature range.
- Long fluid life with a high degree of oxidation resistance.
- Excellent protection against rusting and corrosion
- Compatible with synthetic rubber seal materials.
- Suitable for certain Audi, Ford, Lexus, Saab, Toyota, Volkswagen and Volvo models.

### **SPECIFICATIONS**

Meets the requirements of:

JWS 3309 / Type T-IV  
Ford WSS-M2C924-A  
Audi G-055-025-A2  
GM 9986195

### **TYPICAL INSPECTION DATA**

Specific gravity at 20 °C	0.851
Viscosity @ 100 °C	7.2 cSt
Viscosity @ 40 °C	35 cSt
Colour	Red
Phosphorus	0.03%

### **HANDLING**

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### **SHELF LIFE**

- Five years from date of manufacture.
- Date of manufacture can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.