



## **XTECH 5w30**

### **APPLICATION**

- Fully synthetic high performance 5w30 oil for Ford DuraTec, DuraTorq and Zetec engines.
- Suitable for petrol and diesel vehicles including fuel injected, multivalved and turbo charged.

### **SPECIFICATIONS:**

- SAE 5w30
- API SL CF
- ACEA A5 B5
- Ford WSS-M2C913-C

### **TYPICAL INSPECTION DATA:**

Specific gravity at 20°C	0.848
Viscosity @ 100°C	10.1 cSt
Viscosity @ 40°C	55 cSt
Viscosity Index	166
Viscosity CCS @ -30°C	4400 cP
T.B.N.	7.8 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.12%
Calcium	0.25%
Phosphorus	0.11%
Colour	Brown

### **HANDLING**

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### **SHELF LIFE**

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.